

## PU PRIMER TRANS

### Single component primer on non porous substrates

#### DESCRIPTION

PU PRIMER TRANS is one component, fast curing transparent primer for PU coatings on non-porous substrates.

#### USES

Primer on ceramic tiles, marble and metal.

#### LIMITATIONS & PRECAUTIONS

PU PRIMER TRANS is flammable. It should be used in well ventilated areas far from naked flames.

In closed spaces, ventilation should be provided and carbon active masks should be used.

#### PROPERTIES

- Quick drying
- One component

#### APPLICATION PROCEDURE

Remove oil, grease and wax contaminants, cement laitance, loose particles and mold release agents. Apply with a cloth. Once cured (10-15 minutes), the top coat can be applied.

#### COVERAGE

100 - 200 gr/m<sup>2</sup> subject to surface porosity.

#### PACKAGING

1 Liter, 5 Liter and 20 Liter

#### SHELF LIFE

Can be kept for 12 months minimum in the original unopened packings in dry places and at temperatures of 5-25°C.

#### TECHNICAL SPECIFICATIONS

PROPERTY	UNIT	METHOD	SPECIFICATION
Flash point	°C	ASTM D93, Closed cup	42
Dry time at (25°C) & 55% RH	min	-	10-15

The information contained herein corresponds to the best of our knowledge. The user must ensure beforehand that this product is suitable for a certain application. The user alone is fully responsible for any consequences deriving from the use of this product.

Made in EU for DECOBUILD SARL under a certified quality management systems ISO 9001 & ISO 14001 & OHSAS 18001